



CL408e COMPARISON



The CL408e brings the latest in technology to the world of thermal transfer label printing. The CL_e Series Printers set new benchmarks in label throughput. A new generation RISC processor provides high performance in label production even when printing directly from standard Windows[®] applications.

- **Fast Processing Speed**
- **Heavy Metal Cabinetry**
- **18MB of Standard Memory**
- **Field installable Plug-In Interfaces**

	SATO	ZEBRA	ZEBRA	DATAMAX	INTERMEC	TEC
MODEL	CL408e	105 Se	Z4M	DMX-I-4206	EasyCoder 3400	B-472
LIST PRICE	\$1695	\$2295	\$1695	\$1695	\$1795	\$1995
PRINT FEATURE						
METHOD	DT/TT	DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
RESOLUTION	203 dpi	203 dpi	203 dpi	203 dpi	203 dpi	203 dpi
SPEED	Up to 6 ips	Up to 6 ips	Up to 10 ips	Up to 6 ips	Up to 6 ips	Up to 10 ips
PRINT WIDTH (max)	4.1" (104mm)	4.1" (104mm)	4.1" (104mm)	4.1" (104mm)	4.1" (104mm)	4.1" (104mm)
PRINT LENGTH (max)	49.2" (1249mm)	15" (381mm)	37" (940mm)	99" (2475mm)	Unlimited	15.1" (384mm)
MEMORY						
RAM	16 MB SRAM	512K DRAM	1 MB RAM	8 MB DRAM	512K DRAM	512K DRAM
NV MEMORY	2 MB Flash ROM			1 MB Flash	128K	256K Flash
CPU	32 BIT RISC	32 BIT	32 BIT RISC	32 BIT		
MEDIA						
ROLL O.D.	8.6" (218 mm)	8" (203 mm)	8" (203 mm)	8" (203 mm)	8.38" (213 mm)	7.9" (200 mm)
STANDARD SENSOR	Transmissive & Reflective	Transmissive	Transmissive & Reflective	Transmissive & Reflective	Transmissive	Transmissive & Reflective
INTERFACE						
PARALLEL	IEEE1284 Bi-directional ⁽¹⁾		IEEE1284 Bi-directional	IEEE1284		Centronics
SERIAL	RS232C ⁽¹⁾ RS422/485 ⁽¹⁾ (up to 57.6K bps)	RS232C RS422	RS232C RS422/485 (up to 38.4K bps)	RS232 (up to 38.4K bps)	RS232C RS422/RS485 (up to 38.4K bps)	RS232C (up to 19.2K bps)
OPTIONAL I/F	USB ⁽¹⁾ Ethernet ⁽¹⁾ Twinax/Coax ⁽¹⁾	Centronics Parallel Ethernet	Ethernet	Ethernet	Centronics Parallel Ethernet Twinax/Coax	Centronics Parallel Twinax/Coax
OTHER						
2-D SYMBOLOGIES	Yes	Yes	Yes	Yes	Yes	Yes
LCD	Yes	N/A	Option	Yes	No	Yes
CABINTRY	Metal	Metal	Metal	Metal	Metal	Metal
OPTIONS						
CUTTER	Option	Option	Option	Option	Option	Option
DISPENSER	Option	Option	Option	Option	Option	Option

⁽¹⁾Plug-In I/F Module. Only one may be installed