



## CL608e COMPARISON



The CL608e brings the latest in technology to the world of thermal transfer label printing. The CLe Series Printers set new benchmarks in label throughput. A new generation RISC processor provides high performance in label production even when printing directly from standard Windows® applications.

- **Fast Processing Speed**
- **Heavy Metal Cabinetry**
- **18MB of Standard Memory**
- **Field installable Plug-In Interfaces**

	SATO CL608e	ZEBRA Z6M	DATAMAX DMX-W-6208	INTERMEC EasyCoder 3600	Printronix T5206
LIST PRICE	\$2995	\$2995	\$3195	\$2595	\$3895
<b>PRINT FEATURE</b>					
METHOD	DT/TT	DT/TT	DT/TT	DT/TT	DT/TT
RESOLUTION	203 dpi	203 dpi	203 dpi	203 dpi	203 dpi
SPEED	Up to 8 ips	Up to 10 ips	Up to 8 ips	Up to 5 ips	up to 10 ips
PRINT WIDTH (max)	6" (152 mm)	6.6" (168 mm)	6.61" (168 mm)	6.6" (168 mm)	6.6" (168 mm)
PRINT LENGTH (max)	49.2" (1249 mm)	23" (584 mm)	99" (2515 mm)	Unlimited	
<b>MEMORY</b>					
RAM	16 MB SRAM	1 MB DRAM	16 MB DRAM	512K DRAM	8 MB DRAM
NV MEMORY	2 MB Flash ROM		2 MB Flash	128K NVRAM	4 MB Flash ROM
CPU	32 BIT RISC	32 BIT RISC	32 BIT		
<b>MEDIA</b>					
ROLL O.D.	8.6" (218 mm)	8" (203 mm)	8" (203 mm)	8.38" (213 mm)	8" (203 mm)
STANDARD SENSOR	Transmissive & Reflective	Transmissive & Reflective	Transmissive & Reflective		
<b>INTERFACE</b>					
PARALLEL	IEEE1284 Bi-directional <sup>(1)</sup>	IEEE1284 Bi-directional	IEEE1284		IEEE1284
SERIAL	RS232C <sup>(1)</sup> RS422/485 <sup>(1)</sup> (up to 57.6K bps)	RS232/422/485 (up to 38.4K bps)	RS232 (up to 38.4K bps)	RS232 RS422/485 (up to 19.2K bps)	RS232/422
OPTIONAL I/F	USB <sup>(1)</sup> Ethernet <sup>(1)</sup> Twinax/Coax <sup>(1)</sup>	Ethernet	RS422 Ethernet	Centronics Parallel Ethernet Twinax/Coax	Twinax/Coax Ethernet
<b>OTHER FEATURE</b>					
2-D SYMBOLOGIES	Yes	Yes	Yes	Yes	Yes
LCD	Yes	Option	Yes	No	Yes
CABINTRY	Metal	Metal	Metal	Metal	Aluminum
<b>OPTIONS</b>					
CUTTER	Option	Option	Option	Option	Standard
DISPENSER	Option	Option	Option	Option	Standard

<sup>(1)</sup>Plug-In I/F Module. Only one may be installed

**SATO America, Inc.** • 545 Weddell Drive • Sunnyvale, CA 94089  
 Phone: (408) 745-1300 • Fax: (408) 745-1309  
 E-mail: satosales@satoamerica.com • web site: www.satoamerica.com