



## CT400/410 COMPARISON



SATO's CT Series printers feature unparalleled processing speed and power in a compact unit. Along with their rugged construction, the CT is an ideal printer for a wide range of labeling applications. The CT printers continue the SATO tradition of designing high quality, high performance thermal bar code printers while delivering exceptional value

- **Fast Processing Speed**
- **Small Footprint**
- **10MB of Standard Memory**
- **High Resolution Print**

	SATO CT400	SATO CT410	ZEBRA Stripe S-600™	DATAMAX Datamax XL
LIST PRICE	DT: \$995 TT: \$1,195	DT: \$1,250 TT: \$1,450	DT: ----- TT: \$1,395	DT \$1,695 TT: \$1,795
<b>PRINT FEATURES</b>				
METHOD	DT/TT or DT only	DT/TT or DT only	DT/TT	DT/TT or DT only
RESOLUTION	203 dpi	305 dpi	203 dpi	203 dpi
SPEED	2 - 6 ips	2 - 4 ips	2 - 6 ips	2 - 6 ips
MAX PRINT WIDTH	4.1" (104mm)	4.1" (104mm)	4.09" (104mm)	4.1" (104mm)
<b>MEDIA</b>				
MEDIA TYPE	Roll/Fanfold	Roll/Fanfold	Roll/Fanfold	Roll/Fanfold
LOADING	Simple Drop-In	Simple Drop-In	Hand Thread	Hand Thread
ROLL O.D.	4.4" (110mm) with 1.5" core	4.4" (110mm) with 1.5" core	8" (203mm) with 3" core	8" (203mm) with 1.5" core
STANDARD SENSOR	See-Through/Reflective	See-Through/Reflective	See-Through/ -----	See-Through/Reflective
<b>STANDARD MEMORY</b>				
RAM	8 MB SRAM	8 MB SRAM	2 MB DRAM	4 MB DRAM
NV MEMORY	2 MB Flash ROM	2 MB Flash ROM	1 MB Flash	4 MB ROM
CPU	32 BIT RISC	32 BIT RISC	32 BIT RISC	32 BIT RISC
<b>INTERFACE</b>				
STANDARD I/F	• IEEE1284 High Speed, Bi-directional Parallel	• IEEE1284 High Speed, Bi-directional Parallel	• RS232 (57.6K bps) • IEEE-1284 Parallel (bi-directional)	• RS232 (38.4K bps) • IEEE1284 Parallel
OPTIONAL I/F	• RS232 (57.6K bps) • USB • LAN/Ethernet/Coax	• RS232 (57.6K bps) • USB • LAN/Ethernet/Coax	• Twinax/Coax • External Ethernet	• RS422
<b>OTHER FEATURES</b>				
2-D SYMBOLOGIES	Yes	Yes	Yes	Yes
WINDOWS DRIVER	Included	Included	Not Included	Not Included
<b>DIMENSIONS</b>				
WIDTH X HIGH X DEEP	7.8" x 9.1" x 7.1"	7.8" x 9.1" x 7.1"	8.25" x 17" x 13"	9.5" x 16.6" x 8.8"
WEIGHT	6.6 lbs. (3 kg)	6.6 lbs. (3 kg)	17 lbs. (7.71 kg)	23 lbs. (10.4 kg)
<b>OPTIONS</b>				
PEEL-OFF	Option	Option	Option	Standard
CUTTER	Option	Option	Option	Option

**SATO America, Inc.** • 545 Weddell Drive • Sunnyvale, CA 94089  
 Phone: (408) 745-1300 • Fax: (408) 745-1309  
 E-mail: satosales@satoamerica.com • web site: www.satoamerica.com