



HT200e - “Easy-To-Use” Stand-Alone Printer

- **Direct Thermal**
- **Stand-Alone or Online**
- **Automatic Calculations**
- **Optional Battery Pack**
- **Easy Supply Loading**
- **Simple To Maintain**
- **Easy To Program**

SATO's new HT200e printer is a new stand-alone printer which has been specially developed to fill the gap between basic hand labelers and large desktop labeling systems. This unique stand-alone machine is extremely user-friendly and prints labels and barcodes at the touch of a button.

It's fast, versatile, easy to use, and provides low cost solutions to a variety of labeling problems in both the retail and industrial sectors.

Designed for the following applications:

- Mark Down Labels
- Sales Tax Calculations
- Price Marking
- General Retail Pricing
- Stock Control
- Sequential Numbering



HT200e Printer

Printing Method:

Direct Thermal

Print Resolution:

203 dpi (8 dots/mm)

Printing Speed:

Up to 2 ips (60mm/sec) Battery Operated

Up to 3 ips (80mm/sec) AC Adapter

Max. Print Area:

1.89" (48mm) W x 3.78" (96mm)

Media Size:

Min. 1.1" (28mm) W x 0.63" (16mm) L

Max. 2" (51mm) W x 4" (103mm) L

Dimensions

5.2" W x 9.06" D x 5.94" H

(132mm W x 230mm D x 151mm H)

Weight:

5.3 lb (2.4kg) without Battery Pack

5.5 lb (2.5kg) with Battery Pack

Features:

- Auto Power off (5 min)
- Calendar (Standard)
- Back lit LCD
(16 Characters x 3 Lines)

Memory:

512K Bytes Flash ROM

2 MB SRAM (optional)

Processor:

32-Bit RISC

Media:

Caliper: 5.5 - 7.48 MIL

Core Diameter: 1" (25.5mm)

Max. Roll O.D.: 2.95" (75mm)

Roll Label Wind: Face-In

Pop Label Wind: Face-Out

Sensing:

Transmissive Sensor for Gaps

Reflective Sensor for I-Marks

Interface Connection:

RS232C Serial Interface

Scanner (RS232C/TTL Factory Select)

Barcode Symbologies:

UPC-A/-E, EAN-8/13, Code39,

Code128, I 2/5, NW-7

Barcode:

2:1, 2.5:1, 3:1 ratio;

bar code height 1 to 240 dots

Human Readable Fonts:

8 fonts including 4 useful POP characters

**Rotation:**

Font: 0°, 90°, 180°, 270°

Barcode: 0°, 180°

Self Check Function:

Paper End; Cover Open; Test Print; Battery Level Check; Head Check

AC Power:

100V/230V; Voltage + 8.4 V (Manual Select)

Consumption: Max. 671VA 43W

Options:

- Battery Pack & Charger
- SRAM Card (2MB)
- Touch or Pen Scanner

SATO America, Inc.

www.satoamerica.com

E-mail: satosales@satoamerica.com

